



ToxiRAE Pro LEL

Personal Wireless Monitor for Combustible Gases and Vapors

The ToxiRAE Pro LEL is the world's first personal wireless combustible gas monitor. The ToxiRAE Pro LEL provides safety professionals with wireless remote access to real-time instrument readings and alarm status for better visibility and faster incident response¹. The ToxiRAE Pro LEL quickly detects and accurately monitors combustibles in concentrations from 0 to 100% of the lower explosive limit (LEL). With the most extensive onboard gas library in its class, the ToxiRAE Pro LEL can be programmed to automatically read in %LEL of the specified compound.

- Wireless elevates safety to the next level
- Man Down Alarm with real-time remote wireless notification
- Easy to maintain with replaceable sensor, filter, and Li-ion battery
- Fully-automatic bump testing and calibration with AutoRAE 2²

Applications

- Construction
- Foundries
- Oil and gas
- Pharmaceutical
- Steel mills
- Utilities
- Water and wastewater
- Welding / hot work

Optional Accessories

- AutoRAE 2 Automatic Test and Calibration System
- Multi-unit charging station for up to five monitors



ToxiRAE Pro LEL Single -Pack Comes With:

- ToxiRAE Pro LEL monitor with sensor, alligator clip, protective rubber boot, and rechargeable battery installed
- Charging and PC communication cradle
- PC communication cable
- AC adapter (100 to 240 V, 50/60 Hz AC to 12 V DC)
- Calibration adapters
- Quick Start Guide
- CD with documentation
- Calibration card, quality certificate, and warranty/registration card

FEATURES & BENEFITS

- Wireless access to real-time instrument readings and alarm status from any location
- Unmistakable five-way local and remote wireless notification of alarm conditions
- 55 built-in LEL correction factors
- Largest display in its class
- Reliable, rugged, and intrinsically safe
- Continuous datalogging
- Easy to use
- Device Management with Honeywell SafetySuite





ISI sa-nv : Instrumentation for Science and Industry

Rue du Doiyenné 3, Dekenijstraat / 1180 Brussels – Belgium

Tel : +32 2 343 30 81 - email : sales@isi-be.eu - Web : hse.isi-be.eu



ToxiRAE Pro LEL Specifications

SPECIFICATIONS ⁴	
SIZE	4.6" H x 2.4" W x 1.2"D (118 x 60 x 30 mm)
WEIGHT	8.29 oz. (235 g.)
SENSOR	Catalytic bead LEL sensor with 0 to 100% LEL range and 1% LEL resolution. Response time (T90) < 15 seconds
DETECTABLE GASES	Combustible gases and vapors from paints, coatings, fuels, degreasers, adhesives, solvents, resins, etchers, inks, pesticides, herbicides, etc. using 55 onboard correction factors
BATTERY	Rechargeable Li-ion battery - Operating time: > 12 hours (normal operation, non-wireless) - Recharge time: < 4 hours through charging cradle
DISPLAY	Graphical LCD display with white LED backlighting (activated when monitor is in alarm or with a button press)
DISPLAY READOUT	- Real-time reading of % of lower explosive limit (LEL); battery status; data logging on/off; wireless on/off and reception quality - Peak values
KEYPAD	2 buttons for operation and programming
SAMPLING	Diffusion
CALIBRATION	Automatic with AutoRAE 2 Test and Calibration System ² or manual
ALARM MODES	- Wireless remote alarm notification ¹ ; audible (95 dB @ 30 cm), vibration, visible alarm (ashing bright red LEDs), and on-screen indication of alarm conditions - Man Down Alarm with pre-alarm and real-time remote wireless notification
DATALOGGING	- Continuous datalogging ³ with a three-month capacity (at one-minute intervals) - User-configurable datalogging interval (from 1 to 3,600 seconds)
COMMUNICATION AND DATA DOWNLOAD	- Data download and instrument set-up on PC via charging and PC comm. cradle - Data download via AutoRAE 2 Automatic Test and Calibration System ² - Wireless data and status transmission via built-in RF modem (optional)
WIRELESS NETWORK	ProRAE Guardian Real-Time Wireless Safety System or Closed-Loop Network with the EchoView Host
WIRELESS FREQUENCY	ISM license-free bands
WIRELESS RANGE (TYPICAL)	ToxiRAE Pro PID to Mesh Router, EchoView Host, or Mesh Reader ² ~ 330 feet (100 meters) ToxiRAE Pro PID to RAELink3 Mesh or RAELink3 Z1 Mesh modems ~ 33 feet (10 meters)
OPERATING TEMPERATURE	-4° to 131°F (-20° to 55°C)
HUMIDITY	0% to 95% relative humidity (non-condensing)
HAZARDOUS LOCATION APPROVALS	CSA:  Class I, Division 1, Groups A, B, C and D. T-code T4 Class I, Zone 0 A/Exia IIC T4 ATEX:  II 1G, Ex ia IIC Ga T4 IECEX: Ex ia IIC Ga T4 China Ex: Ex ia IIC T4
CE COMPLIANCE (EUROPEAN CONFORMITY)	EMC directive: 2004/108/EC. R&TTE directive: 1999/5/EC. ATEX directive: 94/9/EC
PERFORMANCE TEST COMPLIANCE	C22.2 No 152 ANSI/ISA-12.13.01
WARRANTY	- Two years on non-consumable components - One year on sensor, fan, battery, and other consumable parts

ORDERING INFORMATION (MODEL: PGM-1820)

- Wireless or non-wireless versions are available¹
- Bulk packages of 10 units are available
- Refer to the Portables Pricing Guide for part numbers for monitors, accessories, maintenance kits, gas, sensors, and replacement parts



1 Wireless units have a functioning RF modem and are ready for wireless deployments; non-wireless units cannot be upgraded to wireless. Additional equipment and/or software licenses may be required to enable remote wireless monitoring and alarm transmission.

3 Available with Industrial Hygiene configurations only.

4 Specifications are subject to change.



ISI sa-nv : Instrumentation for Science and Industry
Rue du Doyenné 3, Dekenijstraat / 1180 Brussels – Belgium
Tel : +32 2 343 30 81 - email : sales@isi-be.eu - Web : hse.isi-be.eu

